

Wastewater Recovery

City West Water - Altona Treatment Plant
Annmarie Tracey & Emily Rahles-Rahbula
September 2014

This is not an ADB material. The views expressed in this document are the views of the author/s and/or their organizations and do not necessarily reflect the views or policies of the Asian Development Bank, or its Board of Governors, or the governments they represent. ADB does not guarantee the accuracy and/or completeness of the material's contents, and accepts no responsibility for any direct or indirect consequence of their use or reliance, whether wholly or partially. Please feel free to contact the authors directly should you have queries.



City West Water™

Overview

- ^ Altona Wastewater Treatment Plant
- ^ Altona Salt Reduction Plant
- ^ Plant Tour




Altona Wastewater Treatment Plant

Annmarie Tracey– Manager Alternative Water Operations




CityWest Water™

Altona Catchment Area





Process Overview




Plant Information

- ^ Built in 1968 and upgraded in 2007
- ^ Site covers 71 acres
- ^ 16ML/d ADWF – annually treats 4600 ML
- ^ Treats sewage from 50,000 people
- ^ Utilises Biological IDEA – Intermittent, Decanted, Extended Aeration Process
- ^ Tertiary cloth filters and UV disinfection provide treatment to a Tertiary level
- ^ Treated effluent serves as feedwater for the SRP rest is discharged to a submerged ocean outfall
- ^ Produces annually 900+ dry tonnes of biosolids



Inlet pump station




Raw Sewage Data

	BOD	Suspended Solids	Ammonia as N	Total Nitrogen	Total Phosphorus	Total Dissolved Solids
Median	160	130	37	47	6	4500
90 th percentile	198	250	43	62	7.3	4900


Figures shown above are for year 2013-14




Inlet Works



SCADA Screenshot



IDEA Reactors – Anoxic Zone



IDEA Reactors – Aeration Zone



IDEA Reactors - Aeration




Flow Balance Tank



Tertiary Cloth Filters



User Mimics Areas Points Alarms Events Trends Notes Documents Reports



UV Disinfection



EPA Licence Limits

Indicator	Units	Limit Type	To Port Phillip Bay
Biochemical oxygen demand (5 day)	mg/L	Annual Median	8
Biochemical oxygen demand (5 day)	mg/L	90th Percentile	16
Suspended solids	mg/L	Annual Median	10
Suspended solids	mg/L	90th Percentile	15
Escherichia Coli	orgs /100ml	Annual Median	200
Escherichia Coli	orgs /100ml	90th Percentile	1000
Ammonia	mg/L	Annual Median	10
Ammonia	mg/L	90th Percentile	NS
Ammonia	mg/L	Maximum	24
Total nitrogen	mg/L	Annual Median	50
Total nitrogen	mg/L	90th Percentile	75
Total phosphorus	mg/L	Annual Median	50
Total phosphorus	mg/L	90th Percentile	75
pH	pH units	Range	6-9
Total residual chlorine	mg/L	Maximum	1
Flow rate	ML/day	Maximum	30



Treated Discharge Outfall



Assets labelled AC may contain asbestos material and therefore works on these assets must be undertaken in accordance with CHS Regulations 2007 (Part 4.2.1).
Warning : City West Water Limited does not guarantee and makes no representation or warranty as to the accuracy or scale of this plan. This company accepts no liability for any loss, damage or injury by any person as a result of any inaccuracy in this plan.



Sludge Thickening & Dewatering



Pinegro



Composted biosolids windrows



Composted biosolids were used to establish the grass in the ATP garden area in 2013



Altona Recycled Water Scheme

Emily Rahles-Rahbula – Manager Altona Salt Reduction Plant




CityWest Water™

Altona Salt Reduction Plant

- ^ Recycled Water Scheme
- ^ Treatment Process Steps and their purpose
- ^ Recycled Water Quality & Regulatory Requirements




Altona Recycled Water Scheme



The Plant

- ^ ASRP or the Altona Salt Reduction Plant produces 2 grades of water for its customers:
 - 5.9MLD of Industrial Water
 - 3.1MLD of Irrigation Water
- ^ The pipeline from the Altona Treatment Plant connects plastics manufacturer Qenos, Koorungal and Sanctuary Lakes Golf Course and Altona Green reserve.



Chemical Storage



^ Chemical Storage Tanks

- Sulphuric Acid
- Hydrochloric Acid
- Sodium Hypochlorite
- Sodium Metabisulphite
- Antiscalant
- Caustic



Feedwater Storage



- ^ 3 ML balancing storage tank to collect decanted treated effluent from the ATP.
- ^ Flow is pumped from the feed water chamber after tertiary cloth filters and UV disinfection.



UF Feed Strainers



^ UF Feed pumps

- 3 duty / 1 standby feed pumps

^ Coarse Screens

- 1 duty / 1 standby
- 250 micron screen
- 24 individual cartridges / strainer
- Automatic Backwashing based on timer &/or differential pressure.



Ultrafiltration



- ^ 4 Trains, each with 108 modules (with expansion capacity to 120 modules)
- ^ Outside-In hollow fiber membranes
- ^ $LRV=3.5$ for protozoa and $LRV=2.2$ for viruses
- ^ Automatic Clean In Place (CIP) System
- ^ First of the Critical Control Points (TMP, Flux, Turbidity & PDT)



CityWest Water™


Cartridge Filters



- ^ Coarse Screen Filters
 - 5 micron cartridge filters
 - 60 filter tubes per vessel
 - 4 vessels in the system
- ^ Protection for the RO membranes
- ^ Situated between low pressure and high pressure RO Feed Pumps.



Reverse Osmosis



- ^ Salt Reduction Step.
- ^ Three 1st Pass RO Trains
- ^ Two 2nd Pass RO Trains

- ^ RO First Pass is Responsible for Pathogen Removal (i.e.. LRV=1.5)
- ^ Second Critical Control Point (Log Reduction of EC; Recovery and Flux)

- ^ Energy Recovery Unit on inter-stage line of the first pass membranes



Degasification



- ^ Degasification – used to raise the pH of product water to neutral (i.e. pH = 7)



Chlorine Disinfection



- ^ Final Step in Pathogen reduction uses Chlorine disinfection.
- ^ Final Critical Control Point (i.e.. Chlorine Contact Time = Chlorine Residual, Temp, pH, Flow)
- ^ pH adjustment (using caustic and lime dosing) is also conducted at this stage.
- ^ Product Water Storage Tanks
 - 3ML Irrigation Water Storage
 - 3ML Industrial Water Storage



Product Water Quality

- ^ Class A Recycled Water – as per Victorian Department of Health Standards
- ^ Requires approximately 6 Log Reduction in Pathogens across the plant
- ^ Supported by a Recycled Water Quality Management System
- ^ Uses HACCP principles
- ^ Critical Control Points are monitored and when deemed out of desired range the plant will automatically stop.
- ^ Continuous Integrity and Operational Monitoring
- ^ Daily Verification through internal laboratory testing



Product Water Delivery



- ^ Qenos - 3.7 Km of 300mm HDPE transfer pipe
- ^ Sanctuary Lakes (+ Altona Green) – 5km of 225mm + 400m of 100mm of HDPE transfer pipe
- ^ Koorringal – 700m of 150mm HDPE transfer pipe.



Thank You



CityWest Water™