



NEXUS



Integrated Resource Management in Asian Cities: the Urban NEXUS

*Joint Brown Bag Seminar – Urban and Water CoPs
Manila, October 2014*

This is not an ADB material. The views expressed in this document are the views of the author/s and/or their organizations and do not necessarily reflect the views or policies of the Asian Development Bank, or its Board of Governors, or the governments they represent. ADB does not guarantee the accuracy and/or completeness of the material's contents, and accepts no responsibility for any direct or indirect consequence of their use or reliance, whether wholly or partially. Please feel free to contact the authors directly should you have queries.



Participating countries:

- **China**
- **Indonesia**
- **Mongolia**
- **Philippines**
- **Thailand**
- **Vietnam**



Participating cities:

- Ba'nan, 920.000
- Rizaho, 2.880.000
- Weifang, 9.000.000
- Pekanbaru 1.000.000
- Tanjungpinang 230.000
- Ulaanbaatar, 1.200.000
- Naga City, 180.000
- Santa Rosa, 330.000
- Chiang Mai, 150.000
- Korat, 180.000
- Da Nang, 900.000



Integrated Resource Management in Asian Cities: the urban Nexus (water, energy, food/land use)


- Time frame: 2013 - 2015
- Political Partner: UN ESCAP (Bangkok, Thailand)
- Implementation Partner: ICLEI Southeast Asia Secretariat (SEAS)
- Financed by BMZ (German Federal Ministry for Economic Cooperation & Development)

Approach:

- Introduction of innovative engineering technologies in the area of waste water and solid waste management, generation of energy, link to (urban) agriculture, EE in/of buildings
- Holistic/integrated urban planning/breaking open of „silo“ thinking (creation of Nexus Task Forces in cities)
- Multi level approach (micro, meso, macro, supraregional)
- Private sector, civil sector, state/communal
- Grounded/concrete demonstration projects/PFS/FS/scaling up



NEXUS Organisational Structure





Sustainable waste water solutions

Vacuum sewer collection system

Source: RoeVac® Vacuum Sewer Systems

Why Vacuum Sewerage Systems?

- Vacuum sewerage systems are reducing the impact on the environment and have the lowest carbon footprint of any municipal sewerage system;
- Vacuum sewerage systems are collecting waste-water by vacuum means, thereby minimizing:
 - Risks to the Environment
 - Odour
 - Diseases
 - Contamination
 - Energy Use
 - Water Use



Sustainable waste water solutions

Vacuum sewer collection system

Source: RoeVac® Vacuum Sewer Systems

Vacuum sewer system



Gravity sewer system



Advantages of vacuum systems for investors and operators:

- Lightweight small diam. sewer pipes, ease of installation;
- Shallow and small trenches;
- No manholes, no lift stations;
- Only one central vacuum station instead of many lift stations;
- Speed of construction is greatly increased;
- Greatly reduced construction costs;
- Flexible pipeline construction;
- Easy to lay pipelines around obstacles



Vacuum Sewer System

for 110 households in the eastern coastal area of Da Nang City

Equipment



Collection chambers 30

ROEVAC® G50 (average 4 households per collection chamber)

- Flexible installation depths
- Every collection chamber is individually adjusted to the depth of the gravity sewer pipe
- Separation between sewage water and valve chamber
- No flooding of controller and valve monitoring unit possible
- Vacuum valve unit remains always clean and hygienic
- Max. 5 gravity pipe connections possible
- Only one vent pipe necessary in case of multiple connections

Bottle neck

- Constructional element which limits the size of solid pieces entering the system
- Smallest diameter of the entire system



Vacuum Sewer System

for 110 households in the eastern coastal area of Da Nang City
European Standard (EN 1091) to prevent clogging

According to EN 1091 the following resistance to blockage test is performed 5 times to show what foreign matter's size and material range can be disposed in the vacuum system without causing blockages.

The following foreign matter shall be placed in the collection sump, piece by piece over 10 cycles, in random order:

- Cotton handkerchiefs: (400 ± 35) mm x (400 ± 35) mm; (15 ± 5) g 2 pieces
- Plastic bag: (300 ± 30) mm x (270 ± 20) mm 1 piece
- Plastic bag: (200 ± 20) mm x (150 ± 15) mm 1 piece
- Metallic crown corks: nominal diameter 25 mm 2 pieces
- Male condom: 2 pieces
- Sanitary towels: by dry weight (40 ± 10) g (number to suit)
- Disposable baby's nappy: complete with water- proof backing, 1 piece by dry weight 45 g


All absorbent material shall be submerged in water for not less than 1 min or more than 3 min before being placed in the sump.



Sustainable waste water solutions

Vacuum sewerage system – outdoor solution

Functional Description





Sustainable waste water solutions

Vacuum sewerage system - outdoor solution

What does it cost ?

- Costs vary depending of network size and project specifications;
- The cost saving factor is the network itself, so a minimum project size is required to be competitive;
- Vacuum sewer systems can achieve up to 25 - 40% cost savings compared to gravity sewer systems, considering all aspects of construction;


Again !

- Vacuum sewerage systems do not require manholes;
- Trenching is limited to average depth of 0.9 - 1.2 m;
- No interim pumping station for large networks in flat terrain;
- Central Vacuum Station and Odour Control;



Vacuum Sewer System

for 110 households in the eastern costal area of Da Nang City



The data for designing the vacuum sewer system:

- Daily waste water: 160l/PE/day
- Peak factor: 3
- Number of plots: 110
- Persons per plot: 4
- Persons (PE) total: 440
- Design peak flow: 2,44l/s



Vacuum Sewer System

for 110 households in the eastern costal area of Da Nang City



09/10/2014



XXX

The drainage channel is under the walkway between the houses.

The vacuum sewer system will be installed here after.



Sustainable waste water solutions

Da Nang, Vietnam, vacuum waste water collection




Sewer pipes



Vacuum Sewer System

for 110 households in the eastern coastal area of Da Nang City
Vacuum pipe network



High-density polyethylene pipes

HDPE (PN 10, SDR 11)


- ∅ 90mm 250m
- ∅ 90mm 50m
- ∅ 110mm 30m
- ∅ 125mm 50m
- ∅ 140mm 100m

- Collection chambers 30 ROEVAC® G50 (average 4 households per collection chamber)



Vacuum Sewer System

for 110 households in the eastern costal area of Da Nang City
Vacuum Station



Compact Station 360

- 3 vacuum pumps 3,5 kW
- 2 discharge pumps 4 kW
- 1 vacuum vessel 3m³, Ø 2m
- Electrical control panel,
(VDE German Standard)



Vacuum versus Gravity Sewer System

for 110 households in the eastern costal area of Da Nang City

INVESTMENT COST OF VACUUM SEWER SYSTEM versus GRAVITY SEWER SYSTEM

Vacuum sewer system				Gravity sewer system				
No.	Items	Description	Unit	Amount	Items	Description	Unit	Amount
				U\$				U\$
1.1	Connection pipe from house to collection chambers	Using pipe uPVC Ø49, 60, 114 with total length is about 10m (based on GIZ calculation on exactly 78 households)	110 houses	35.631,67	Connection pipe from house to manhole	Pipe connection to front of the house; Using pipe uPVC Ø60, 90, 114 with average length using for one house is 51m	110 houses	113.419,90
1.2	Construction cost of vacuum sewer system	Using 30 collection chambers type RoVac ® G50 along the network; Using one vacuum station to pump wastewater to SPS2 Total length of vacuum network is 735 m; (using HDPE D90, 110, 125, 140) Using 580m pressure pipe HDPE D90 to pump wastewater from VS to SPS2	system	42.488,84	Construction cost of gravity sewer system	Using 48 manhole along the network; Using 9 lift stations Total length of gravity network is 890 m; (using HDPE D200, HDPED300, HDPED400) with 2.5%gravity slope Total pressure pipe to transfer wastewater from lift station 9 to SPS2 is 600m; (using HDPE D90)	system	193.304,54
1.3	Equipment cost of vacuum sewer system	Using one vacuum station (incl. 3 vacuum pumps 3,5kW, 2 discharge pumps 4,0kW, 1 vessel 3m3)	system	153.187,12	Equipment cost of gravity sewer system	Using 9 trash screening 0,5x0,5x1,5m Using 18 submerge pump 4kw	system	127.224,06
TOTAL (before Tax, without overhead / indirect costs and profit)				292.949,00				549,591



Vacuum Sewer System

for 110 households in the eastern costal area of Da Nang City


Annual Operation and Maintenance Costs

Operation and maintenance costs per year VACUUM SEWER SYSTEM versus GRAVITY SEWER SYSTEM		
Labour	<ul style="list-style-type: none"> Annual check of collection chambers; Regular check of vacuum station Optional air treatment only at vacuum station (biofilter) 	<ul style="list-style-type: none"> Regular check of manholes Pipeline inspection, CCTV inspections Cleaning accumulated sludge, slime and debris (jetting with high-pressure)
Repair/ Replacement	<ul style="list-style-type: none"> Oil and filters to vacuum pumps Valve parts (few pieces, membranes) 	<ul style="list-style-type: none"> Oil discharge pumps and lifting stations Manhole / sewer rehabilitation
Energy consumption	<ul style="list-style-type: none"> Only energy consumption at vacuum station; Using one electrical station. 	<ul style="list-style-type: none"> Energy consumption at pumping station; At each pumping station there must be operation power and standby power.
Maintenance	<ul style="list-style-type: none"> Vacuum sewer mains are self-cleaning due to high velocity 	<ul style="list-style-type: none"> H₂S (hydrogen sulphide) deodorization Flushing the pipe network
Wastewater treatment	<ul style="list-style-type: none"> Only wastewater Better aerated waste water Closed system – handles only wastewater of the community (no infiltration) 	<ul style="list-style-type: none"> Handle big amount of infiltrated ground water Handle aged and possibly septic wastewater Handle wastewater from suspicious sources Exfiltration risk
Operation & Maintenance costs	6,611.45 U\$/year	24,155.30 U\$/year



Sustainable waste water solutions

Vacuum sewerage system – biogas production





Sustainable waste water solutions

Vacuum sewerage system – urban agriculture



Vegetables fertilized by the digested black water,
Chentang Village, in Chengdu City, Jiangsu Province of China

- Irrigation of agriculturally used areas
- No further energy intensive treatment necessary
- Nitrogen and phosphate remain in the irrigation water as fertiliser



Urban agriculture in Da Nang, Vietnam



Sustainable waste water solutions

Vacuum sewerage system – soil production

- The remaining sludge after the anaerobic treatment is not contaminated with heavy metal
- The sludge can be used directly for agricultural purposes
- The sludge can be dewatered and grated up to top soil fertiliser



Conditioning of sludge after digestion





As a federal enterprise, GIZ supports the German Government in achieving its objectives in the field of international cooperation for sustainable development.

Published by

Deutsche Gesellschaft für
Internationale Zusammenarbeit (GIZ) GmbH

Registered offices, Bonn and Eschborn, Germany

“Integrated Resource Management in Asian Cities:
the Urban Nexus”

United Nations Building

Rajadamnern Nok Avenue

Bangkok 10200, Thailand

T +66 89 832 1055

E ruth.erlbeck@giz.de

I www.giz.de

Responsible

Ruth Erlbeck

Author

Ralph Trosse

Photo credits

© GIZ/Bilfinger Water Technologies

Layout

Ralph Trosse

In cooperation with

