

# SWM Case Study

## Pre-FS for Denpasar City, Indonesia

This is not an ADB material. The views expressed in this document are the views of the author/s and/or their organizations and do not necessarily reflect the views or policies of the Asian Development Bank, or its Board of Governors, or the governments they represent. ADB does not guarantee the accuracy and/or completeness of the material's contents, and accepts no responsibility for any direct or indirect consequence of their use or reliance, whether wholly or partially. Please feel free to contact the authors directly should you have queries.



# Agenda

- 01** About HEC
- 02** Why SWM?
- 03** SWM Concept
- 04** SWM for Denpasar



## Hankuk Engineering Consultants

<b>Year Established</b>	<ul style="list-style-type: none"> <li>● August 13, 1991</li> </ul>
<b>Number of Employees</b>	<ul style="list-style-type: none"> <li>● 150</li> </ul>
<b>Capabilities</b>	<ul style="list-style-type: none"> <li>● Annual Turnover for Last 10 years <b>25 Mil US\$ (Ave.)</b></li> <li>● Annual Number of Projects for Last 10 years <b>130 Projects (Ave.)</b></li> </ul>



### Types of Services

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● FEASIBILITY STUDY</li> </ul>                         | <ul style="list-style-type: none"> <li>● PLANNING</li> </ul>                      |
| <ul style="list-style-type: none"> <li>● BASIC DESIGN</li> </ul>                              | <ul style="list-style-type: none"> <li>● DETAILED DESIGN</li> </ul>               |
| <ul style="list-style-type: none"> <li>● CONSTRUCTION MANAGEMENT &amp; SUPERVISION</li> </ul> | <ul style="list-style-type: none"> <li>● ENVIRONMENT IMPACT ASSESSMENT</li> </ul> |
| <ul style="list-style-type: none"> <li>● ENGINEERING CONSULTING SERVICES</li> </ul>           |   |



## Water Supply



Advanced Water Treatment Facilities of Gangbuk WTP

## Wastewater Treatment



Water Quality Restoration Center & Clean Energy Center in Multifunctional Administrative City

## Water Resources



Basic plan of Youngju Dam

## Urban Planning




Development(Section 5) Project of Cheongna District in Incheon FEZ




## Climate Change in Korea

### Change of Apple Cultivation Region



### Projected Climograph based on emission scenario






## Climate Change Impacts on Water Problems

- Changing into Subtropical climate
- Frequent, Extended drought alternating with spells of heavy rainfall

- Water availability
- Extreme events
- Operational reliability
- Water quality



We need more efficient and sustainable method for water security



## SWM enables to

### Maximization of Limited Water Resources

SWM provides the optimal utilization system by combining every water resource available. water can be provided and reused wherever necessary without construction of large scale infrastructures

### Preventing Leakage incidents through Comprehensive Monitoring

SWM is capable of identifying leakage incidents through information collected from smart devices. Improved response time to incident and pressure management is reducing the risk of incidents

### Facilitation of Water and Energy Savings

SWM is capable of accurately predicting the needs and appropriate coordination of production and supply through the ICT-based analysis. As such, water and Energy savings can be promoted.



## Basic Concept of SWM

- SWM, an integrated water supply mgmt. for improving O&M
  - ✓ This customized solution is integration of systems, software & smart devices
  - ✓ AMI is consisted of combination of Smart Meter, SCADA & Network sensors.
  - ✓ SWM is a fully tailor-made solution to solve water scarcity & inefficiency



**Hourly usage & water flow data acquisition**



**Analysis min. night flow & optimized operation**




**Pipe inspection (Sahara, NQ-15, W-PIS100)**





## Basic Concept of SWM

Suggesting 3-step Framework for other Countries






## Basic Concept of SWM – 1<sup>st</sup> Step

Focus on countries operating basic facilities

### Improving network management




Establishing **DMA** and building a **water network model** and **D/B** by digitalizing data  
Installing minimum meter(logger type) and sensor considering technical and economical issues in local area

**Co-work** with local engineer with the **technical training and support program**

### Main Objective of 1<sup>st</sup> Step

Initial NRW, Monthly NRW management(water audit), Water network analysis






## Basic Concept of SWM – 2<sup>nd</sup> Step

Focus on countries requiring operation system for sensors

### Near-time monitoring system




Upgrade water network with **wireless sensors and meters**

Install more meters and water quality sensors at main pipe and big customer

Operating **monitoring system** based on **near-time**(hour interval) for low power design

### Main Objective of 2<sup>nd</sup> Step

Water network analysis, Daily auto leak detection with minimum night flow analysis






## Basic Concept of SWM – 3<sup>rd</sup> Step

Focus on countries requiring SWM with smart meter

### Smart water management




Establish Advanced Metering Infrastructure (**AMI**)

Install Smart Meters on every tap and provide information to customer (**smart phone app**)

**Remote control** main valve and upgrade to real-time monitoring system

### Main Objective of 3<sup>rd</sup> Step

Real-time water network analysis, NRW management, auto leak detection with smart meter





## Smart Water Management Project

- AWC's 1st Water Project (HEC, K-Water, Wareco)
- Smart Water Management Project including Non-revenue Water Reduction in Denpasar City






## Status of Denpasar Water Supply

Capacity (L/s)	WTP(L/S)	700
	20Deep well (L/S)	476
	Water from other province	70
	Total(L/S)	1,246
Water Supplied(L/S)		1,251
Water Billed(L/S)		794
Total Population(Ppl)		880,600
Served Population(Ppl)		401,125
Water Coverage (%)		45.6
NRW(%)		36.5
Lpcd	Consumed	171
	Supplied	269
Average Water Tariff (Rp./m <sup>3</sup> )		4,382

Note) 2015 Data





## Findings and Suggestions

Findings	Suggestions
<ul style="list-style-type: none"> <li>➤ No hierarchy between trunk main, distribution pipes and house connections.</li> <li>➤ There are CAD drawings representing transmission and distribution pipelines. But the pipes and appurtenances may not updated regularly with field verification.                             <ul style="list-style-type: none"> <li>• Enough staffs are required to manage updating and logging repair data</li> </ul> </li> </ul>	<p>GIS(SIDAB) Update</p>
<ul style="list-style-type: none"> <li>➤ Insufficient water production capacity and very high load factor</li> <li>➤ NRW tends to be increased.</li> <li>➤ Detailed assessment of water balance is required with calibration of flow meters</li> </ul>	<p>DMA Establishment</p>
<ul style="list-style-type: none"> <li>➤ Lots of ACP and Aged (over 30years) pipes.                             <ul style="list-style-type: none"> <li>• ACP : 94,172m, Old pipe(Installed Before 1986) : 157,534m of over 4" pipes</li> </ul> </li> </ul>	<p>Rehabilitation based on pipe condition assessment</p>
<ul style="list-style-type: none"> <li>➤ PDAM Denpasar has only monitoring system</li> <li>➤ With the DMA establishment, PDAM needs SCADA system</li> </ul>	<p>Integrated Control Center</p>
<ul style="list-style-type: none"> <li>➤ Training Program for PDAM Staffs will be required for DMA management, Consumer relation(meter reading, billing), GIS management, Asset management and so on.</li> </ul>	<p>Human Resources</p>
<ul style="list-style-type: none"> <li>➤ Considering the road, traffic conditions, it is very difficult to construct DMAs or to rehabilitate pipes and extensive complaints are expected.</li> <li>➤ Temporary stoppage of water supply to some local area may happen during implementation</li> </ul>	<p>Support from central, provincial government and coordination with other departments are prerequisite</p>



## Technical Proposal from preliminary Study

### Key Challenges

- ✓ No Pipes Information Update
- ✓ Non-revenue Water and High Load
- ✓ ACP and Aged Pipes
- ✓ Monitoring System Only
- ✓ Insufficient Management Capabilities

### Proposal

- ✓ GIS update with field verification
- ✓ Establishment of DMAs
- ✓ Rehabilitation of Infrastructures
- ✓ Integrated Control Center
- ✓ Capacity Building

### Expected Outcome

- ✓ 36.5% → 15~20% NRW, which is able to save and secure 6.5 million m<sup>3</sup>/year or more
- ✓ Operation Cost Reduction, Enhanced Water Supply, Customer Satisfaction



## Project Components

- Extensive Field investigation and DMA establishment have high priority
- Rehabilitation of pipe network and GIS will be implemented in later phase

Project Components		Cost (million US\$)
1	Field investigation, Design, Construction Supervision	7,0
2.	GIS system update	6,7
3.	<b>DMA system Establishment</b>	<b>5,1</b>
4.	<b>Rehabilitation of Facilities (with DMA construction)</b>	<b>19,5</b>
5.	Replacement of Pipes (after condition assessment)	12,1
6.	<b>SWM System establishment</b>	<b>3,7</b>
7.	TA(Technical Assistant)	3,0
8.	Human Resources(Capacity Building)	0,5
9.	Contingency	-
<b>Total</b>		<b>57,6</b>



## Project Schedule

### Phase I (2016)

- Challenge Recognition
- Pre-Feasibility Study
- 0.1mil. USD

### Phase II (2017-19)

- Feasibility Study
- Pilot Project
- 1~4mil. USD

### Phase III (2020-22)

- DMA, Rehabilitation
- Smart Water System
- 25~53mil. USD above



## Expected Results

Items	Current	SWM
<b>Decision Times</b>	Slow, maybe several weeks (guessed decision)	Days (informed decision)
<b>Performance indicators</b>	Yearly ~ several times a yr.	Monthly ~ daily
<b>Control room</b>	No	24 hours a day
<b>Control of Water input/output</b>	No or Monthly	Daily ~ Real time
<b>Leakage, Pressure control</b>	No	Systematic
<b>Control of Night Flows</b>	No	Real time
<b>Response to burst</b>	Month ~ Week	Day ~ Hour
<b>NRW</b>	35% or more	15~20%



## **Benefits of SWM Project**

- Opportunity costs in terms of NOT implementing SWM project
  - Additional investments for extending water supply facilities due to water loss
  - Capital costs : 25 million USD
    - Intake Pump Station, Water Treatment Plant :  $Q= 30,000\text{m}^3/\text{d}$
    - Storage Reservoir :  $V=9.000\text{m}^3$
    - Pipelines for enlargement of diameter to cope with additional supply
  - O & M costs of additional water supply due to NRW
    - $2.794\text{Rp}/\text{m}^3=0.21\text{USD}/\text{m}^3$  (based on 2016 Denpasar PDAM Data)
- Preventing potential damages to properties and other utilities
- Preventing possible deterioration of water quality