This is not an ADB material. The views expressed in this document are the views of the author/s and/or their organizations and do not necessarily reflect the views or policies of the Asian Development Bank, or its Board of Governors, or the governments they represent. ADB does not guarantee the accuracy and/or completeness of the material's contents, and accepts no responsibility for any direct or indirect consequence of their use or reliance, whether wholly or partially. Please feel free to contact the authors directly should you have queries.










RECEERING



PRC's Greenhouse gas emissions and Commitment to Climate Change

-Carbon peaking by 2030 -carbon neutrality by 2060



Source:https://climateactiontracker.org/countries/china/

Xiangtan, Hunan in the People's Republic of China

- An old industrial town undergoing rapid urbanization and industrial transformation
- Designated low-carbon city since 2018
- Population: 2.9 million
- GDP per capita in 2018:


CNY 75,609

(ranking: 69th in 2017)









Low-Carbon Development (working definition)

Low-Carbon Development refers to 'sustainable development' grounded in systems-thinking and guided by quantifiable indicators of GHG emissions, which encourages integrated and collaborative city planning, coherent sector development, resilience improvement by taking preventive approach, and active governance through engaging and activating all stakeholders by providing the right incentives.

- · Motivation for change
- LC actions shall be easy
- Power, resources, and information/knowledge

"Low-carbon and resilient city must benefit its residents and their wellbeing. Through improvement of livability, citizens shall be proud of their city!"


















Integrated Program Design to Activate all Actors



Investment Project

Output 1: Lowcarbon & resilient infrastructure

- -transport/mobility-green Building
- -clean energy
- -urban space and connectivity




Output 3: Capacity building and Knowledge Enhanced



Output 2: Information & knowledge platforms



Smart Xiangtan










Policy and Reforms to support and sustain the transformation and behavior changes







Implementation Arrangement


Xiangtan Municipal Government


Program Management Office (led by Secretary General of XMG)

Municipal Bis Data Longer Conservation Rule Bureau Bureau Houstief Bureau Bureau Harion And Bureau Bureau Franchion Bureau Burea











INTERNAL. This information is accessible to ADB Management and staff. It may be shared outside ADB with appropriate permission.



Results	i= 	Results	i≡ •••
Climate		Climate	
Storage capacity:		Storage capacity:	48.29 m3
Return time factor:		Return time factor:	8.26 +1
Groundwater recharge:		Groundwater recharge:	170 mm/year
Evapotranspiration:		Evapotranspiration;	51.65 mm/year
Heat reduction:		Heat reduction:	0.07 C
Cool areas:		Cool areas:	0
Cost		Cost	
Construction:		Construction:	10348 €
Maintenance:		Maintenance:	103 €/year
Water quality		Water quality	
Pathogen reduction:		Pathogen reduction:	0 %
Nutrient reduction:		Nutrient reduction:	0 %
Adsorbing pollutants:		Adsorbing pollutants:	0 %



Permeable pavement (infiltration & storage)



Permeable pavements consist of porous material that absorbs rainfall. Water can be stored either in the top layer (e.g. very open asphalt concrete) or in below the top layer in the foundation. Besides reducing runoff, permeable pavements can trap suspended solids and filter pollutants from the water.



Rain garden



These are sandy soil or aggregate filled depressions that treat stormwater runoff to improve water quality. Stormwater is captured and allowed to percolate through the soil/aggregate layer, where pollutants are removed, prior to being released through an underdrain located at the bottom of the depression.



Infiltration trench



An infiltration trench, also known as a French drain, is a linear feature used to reduce stormwater runoff and improve water quality. These shallow excavated trenches are filled with aggregate or crushed stone that is designed to allow for stormwater to infiltrate the ground plane and ultimately percolate though permeable soils into the groundwater. Their linear shape can also serve to convey stormwater from one area



Infiltration boxes



Infiltration boxes buffer rainwater underground and allow using a single area for two purposes. In general they offer more storage capacity than above-ground infiltration installations. More rainwater can be buffered temporarily and gradually released into the groundwater. The extra infiltration leads to less drought damage, subsidence and salinization.



mission.

Creating shade



Creating shade is important to prevent surfaces from heating up and to cool the surroundings. This can be accomplished by using trees, pergolas, overhangs, awnings and such. Arcades and covered walkways are urban elements commonly used in warm countries to create shade.



Rainwater detention pond (wet pond)



Buffer ponds temporarily capture precipitation and allow it to drain off slowly. During rainfall, the rainwater is captured in the pond and subsequently drained off to create room for the next precipitation. Buffer ponds can be designed to have a mostly stony or a mostly natural appearance.



Green roof with drainage delay



Green roofs with drainage delay are also called retention roofs. It is a green roof that can store extra water in a substrate layer under the green planted layer and is drained delayed with a pinched drain. A polder roof is a retention roof where the control system is linked to the weather forecast.



Systems for rainwater harvesting



Rainwater harvesting is the collection and storage of stormwater for reuse on site. This is most commonly be achieved by capturing runoff from the roof of a building, however, it can also include the collection of runoff from throughout the site or byproducts from systems such as air conditioning condensate. The collection structures can take on multiple forms and be installed either above ground or subsurface. Depending on its source and treatment, the harvested water can be reused on site for irrigation.





